SPECIFICATION

Range: BAFFLE DIRECT Design: Marc Sadler

"Snowsound Technology" sound-absorbing element, ceiling fixing.

Panel description:

Both faces with convex section 36 mm thick, consisting of an internal padding in variable density polyester fiber. The density decreases moving towards the heart of the panel, which is covered on both sides with Trevira CS® polyester fabric, solidly applied to the padding. The panel is double sided, with same characteristics on both sides. It is characterized by the rigid edge obtained by the manufacturing process itself, without any supporting and/or stiffening frame.

The panel has Euroclass B-s2, d0 fire reaction.

The panel is Greenquard Gold certified, which validates its low VOC emission and its contribution to the quality of the indoor environment.

The panel is 100% recyclable and has no detectable formaldehyde content according to UNI EN 717-2. It does not contain felts or other organic materials that are hardly recyclable.

The panel has been tested in reverberation chamber according to UNI EN ISO 354 and obtained "Acoustic Absorption Class A", in accordance with UNI EN ISO 11654.

Panel dimensions: 75x44 cm

> 119x44 cm 139x44 cm 159x44 cm 179x44 cm

Fixing kit description:

The ceiling fixing kit consists of two cylindrical elements, made of chrome-plated metal ø 12 mm, which embrace the edge of the panel. These elements allow, by means of 14x50 mordant screws fixed into the edge of the panel, direct joining without the aid of other accessories. To these elements are attached, respectively: two M26 male/female threaded cylindrical elements and an internal threaded element that has a countersink for the passage of the ceiling fixing screws.

A chromium-plated steel ring nut knurled on the outside is screwed to this element.

product standard EN 13964 for the intended use as a drop ceiling.

The products described in this data sheet are **CE marked** according to the harmonized





Available colors:



