

MITESCO WALL

SPECIFICATION

Range: MITESCO

Design: Michele De Lucchi

"Snowsound Technology" sound-absorbing element fixed to the wall.

Panel description:

Both faces with convex section 36 mm thick, consisting of an internal padding in variable density polyester fiber. The density decreases moving towards the heart of the panel, which is covered on both sides with Trevira CS® polyester fabric, solidly applied to the padding. The panel is double sided, with same characteristics on both sides. It is characterized by the rigid edge obtained by the manufacturing process itself, without any supporting and/or stiffening frame. The panel is equipped with two series of punched holes for anchoring to the appropriate supports.

The panel has **Euroclass B-s2, d0** fire reaction.

The panel is **Greenguard Gold** certified, which validates its low VOC emission and its contribution to the quality of the indoor environment.

The panel is **100%** recyclable and has no detectable formaldehyde content according to UNI EN 717-2. It does not contain felts or other organic materials that are hardly recyclable.

The panel has been tested in reverberation chamber according to UNI EN ISO 354 and obtained "**Acoustic Absorption Class A**", in accordance with UNI EN ISO 11654.

Panel dimension: 75x44 cm

119x44 cm 159x44 cm

All formats can be used both vertically and horizontally










Two pairs of techno polymer supports are fixed through the panel holes. Visible on both sides, covered on the front by a techno polymer casing. A stiffening bar, made of epoxy powder coated steel, is fixed both to the rear supports and directly to the panel through screws. The panel can be fixed to the wall using epoxy powder coated spacers (3mm thick) or directly by means of special screws.





Available colors:





Caimi Brevetti S.p.A. reserves, by its unappealable judgment, the right to modify without prior notice the building materials, the technical and aesthetic specifications, as well as the dimensions of the products in this technical sheet, where pictures are purely as an indication.