

PLI OVERSIZE SOLVED

SPECIFICATION

Range: PLI OVERSIZE Design: Marc Sadler

"Snowsound Technology" sound-absorbing free-standing element .

Panel description:

Both faces with convex section 36 mm thick, consisting of an internal padding in variable density polyester fiber. The density decreases moving towards the heart of the panel, which is covered on both sides with Trevira CS® polyester fabric, solidly applied to the padding. The panel is double sided, with same characteristics on both sides. It is characterized by the rigid edge obtained by the manufacturing process itself, without any supporting and/or stiffening frame.

The panel has Euroclass B-s2, d0 fire reaction.

The panel is Greenquard Gold certified, which validates its low VOC emission and its contribution to the quality of the indoor environment.

The panel is 100% recyclable and has no detectable formaldehyde content according to UNI EN 717-2. It does not contain felts or other organic materials that are hardly recyclable.

The panel has been tested in reverberation chamber according to UNI EN ISO 354 and obtained "Acoustic Absorption Class A", in accordance with UNI EN ISO 11654.

Panel dimensions: 119x59 cm 119x119 cm 119x159 cm

> 159x59 cm 159x119 cm

Bases description:

Each panel is supported by an epoxy powder coated steel stand composed of a metal base (6 mm thick sheet) with two welded elements (rectangular section 25x15mm, 2mm thick) and by two transparent techno polymer feet fixed to the edge of the panel with self-tapping screws.

Belts description:

Pair of elastic belts, made of techno polymer, equipped with steel buttons and eyelets used for joining panels.











Available colors:



Available colors for belts:

