

# 

# SPECIFICATION

## Range: **TRA LIGHT** Design: **Marc Sadler**

"Snowsound Technology" sound-absorbing element, suspended from the ceiling with cables.

### Panel description:

Both faces with convex section 36 mm thick, consisting of an internal padding in variable density polyester fiber. The density decreases moving towards the heart of the panel, which is covered on both sides with Trevira CS® polyester fabric, solidly applied to the padding. The panel is double sided, with same characteristics on both sides. It is characterized by the rigid edge obtained by the manufacturing process itself, without any supporting and/or stiffening frame.

The panel has Euroclass B-s2, d0 fire reaction.

The panel is **Greenguard Gold** certified, which validates its low VOC emission and its contribution to the quality of the indoor environment.

The panel is **100% recyclable** and has no detectable formaldehyde content according to UNI EN 717-2. It does not contain felts or other organic materials that are hardly recyclable.

The panel has been tested in reverberation chamber according to UNI EN ISO 354 and obtained "**Acoustic Absorption Class A**", in accordance with UNI EN ISO 11654.

| Panel dimensions: | 75x44 cm   | 59x59 cm  | 119x119 cm |
|-------------------|--|-----------|------------|
|                   | 119x44 cm  | 75x59 cm  | 159x119 cm |
|                   | 139x44 cm  | 119x59 cm |            |
|                   | 159x44 cm  | 159x59 cm |            |
|                   | 179x44 cm  |           |            |
|                   | All formats can be used both vertically and horizontally |           |            |

### Fixing kit description:

The fixing kit consists of two elements made of epoxy powder-coated zama, which are fixed to the upper corners of the panel with self-tapping screws. A cylindrical stainless steel cable-clamp protrudes from these elements, featuring a hole for the passage of the cables. This maintains the panel in a perpendicular position with respect to the floor. The steel cables ( $\emptyset$  3 mm L 4 m) are equipped with galvanized steel terminals at the lower ends while are fixed at the top with two connections in chromed steel. Each connection is composed of a plate  $\emptyset$  34.5 mm, featuring a hole for ceiling mounting and a cable holder  $\emptyset$  21.5 x 35 mm connected together with a M16 nickel-plated threaded bush.

The products described in this data sheet are **CE marked** according to the harmonized product standard EN 13964 for the intended use as a drop ceiling..





Caimi Brevetti S.p.A. reserves, by its unappealable judgment, the right to modify without prior notice the building materials, the technical and aesthetic specifications, as well as the dimensions of the products in this technical sheet, where pictures are purely as an indication.


# Available colors:



### Fixing indications:

For panels with one side size 44 cm or 59 cm max 4 pieces for each pair of cables.





119x44 / 159x44

119x59 / 159x59

119x119 / 159x119 cm

119x44 / 159x44

119x59 / 159x59

119x119 / 159x119 cm



Caimi Brevetti S.p.A. reserves, by its unappealable judgment, the right to modify without prior notice the building materials, the technical and aesthetic specifications, as well as the dimensions of the products in this technical sheet, where pictures are purely as an indication.